

## BSU with Manual Raising and two lights

Set of one triangle and two lights

Article number : 22536



### Set of one triangle and two lights

#### Technical specifications :

- Metal mounting with length :
- 1.2 m for one triangle and two lights
- Anti-corrosion treatment - 2 point adhesive, Installation on any type of vehicle
- Delivered with 6m cable harness, switch and fuse
- System for manually locking and raising the triangle
- 500 or 700 triangle
- *Delivered with double-sided triangle (AK5) with LED lights, with a diameter of 74 mm . (Dual voltage for all-LED models)*
- *Model in 24V also available*

#### Models available :

Set of 1 triangle and two lights	Article# in class 1	Article# in class 2
Mounting with 1 triangle 500 and 2 amber halogen rotating lights 55W	22536	22548
Mounting with 1 triangle 700 and 2 amber halogen rotating lights 55W	22537	22549
Mounting with 1 triangle 500 and 2 amber rotating Gyroled	22538	22550
Mounting with 1 triangle 700 and 2 amber rotating Gyroled	22539	22551
Mounting with 1 triangle 500 and 2 amber flashing Gyroled	22540	22552
Mounting with 1 triangle 700 and 2 amber flashing Gyroled	22541	22553

<b>Colour LEDs</b>	White
<b>Colour lens</b>	Ambar
<b>No. of LEDs</b>	3 Amber 74 mm LED light : 964 candela photometry
<b>Voltage</b>	10-30V
<b>Consumption</b>	1.2A : 10/15V 360mA : 24V
<b>Height</b>	500mm or 700mm
<b>Operating temperature</b>	-30°C - +85°C
<b>Includes</b>	6m cable harness, switch and fuse