

Standby-Mercura 4 Rue Louis Pasteur ZA Les Gailletrous 41260 LA CHAUSSEE SAINT VICTOR - FRANCE Tél. +33(0)2 54 57 52 52 - Fax +33(0)2 54 56 80 00 - export@standby-mercura.fr - www.standby-mercura.fr

## **Encased Scrolling Lightbar**

Amber Scrolling single-sided lightbar 1.10m - 12V Article number : 21743



These lightbars are intended for reinforcing the signalling of the position response or work vehicles.

The RDF74s are equipped with five or seven LED warning lights.

## **Technical specifications:**

Amber Scrolling single-sided lightbar 1.10m

Lightbar of 1.10m and 1.50m, 1 side, amber casing, 145mm height Lightbar of 1.10m and 1.50m, 2 sides, amber casing, 175mm height 5 amber LED traffic director LED lights with a diameter of 74mm Supplied with:

Mounting brackets for roof panel, and scrolling unit.

The 8 key keypad supplied with the lightbar, can be used to control the following functions:

- Special amber beacons (Gyroled, flashing beacons, halogene beacons according to the option)
- 3 keys for direct access to approved scrolling on the public highway (from the right to the left, full bar - Warning)
- 1 key for accessing 3 other warning beacons mode (from the centre out <-x-> Bi-signal, Random)
- 1 auxiliary key for connecting an additional electrical component (additional rotating light, work spotlight, etc., not included)
- 1 triangle key for connecting an additional electrical triangle (triangle not included)

Day/night detection cell

Input voltage: 12 V (for 24 V: Article# 21744)

## **Approvals:**

NF EN12352 classification: classes L2H, C1, F2, O1, T1

## Other models available:

	RDF74							
Length	1.10m	1.50m	1.10m	1.50m	1.10m	1.50m	1.10m	1.50m
Two rotating lights	х	х	yes	yes	х	х	х	х
Two rotating Gyroleds	х	х	х	х	yes	yes	х	х
Two flashing Gyroleds	х	х	x	х	х	х	yes	yes
Single-sided	yes							
#Article 12V	21743	21745	21747	21749	22996	22997	22998	22999
#Article 24V	21744	21746	21748	21750	24943	24944	24945	24946

**Lens** Polycarbonate

Colour LEDs White
Colour lens Amber

**No. of LEDs** 5 amber LED traffic

director LED lights with a diameter of 74mm

Flash Patterns Rotating

Voltage 10-30V

**Length** 1.10 m or 1.50 m

**Approval** ECE R65 I

	RDF74							
Length	1.10m	1.50m	1.10m	1.50m	1.10m	1.50m	1.10m	1.50m
Two rotating lights	x	х	yes	yes	х	х		
Two rotating Gyroleds	x	х	x	х	yes	yes	х	х
Two flashing Gyroleds	x	х	x	х	х	х	yes	yes
Double-sided	yes	yes	yes	yes	yes	yes	yes	yes
#Article 12V	21751	21753	21755	21757	B23000	B23001	B23002	23003
#Article 24V	21752	21754	21756	21758	24947	24948	24949	24950