

LED Bar FL12A

High-brightness bar on anodised aluminium frame

Article number : 24651



Technical specifications :

- High-brightness bar on anodised aluminium frame
- Different mountings available (bracket mounting, flush mounting...)
- Protection rating : IP67
- Operating temperature from -40°C to +60°C
- 4 x 3 led light units (12 leds) - Dimensions in mm: 336 x 39 x 90
- 2 x 3 led light units (6 leds) - Dimensions in mm: 175 x 39 x 90
- Inside mounting : provided with anti-glare housing and suction pads for windshield or rear window mounting
- Cigar lighter plug with switch (cable length : 3,45 m)
- Consumption : < 1A for 2 units (depends on the scrolling mode selected)
- Flashing mode change by button
- Large choice of flashing modes : 21 flashing modes (4 lights) 33 flashing modes (2 lights)

Lens	Polycarbonate
Colour LEDs	White
Colour lens	Amber
No. of LEDs	4 x 3 led light units (12 leds) 2 x 3 led light units (6 leds)
Flash Patterns	21 flashing modes (4 lights) 33 flashing modes (2 lights)
Cable	3.45 m
Consumption	< 2 A for 8 units
Dimensions	12 LEDs : 336 x 39 x 90 mm 6 LEDs : 175 x 39 x 90mm
Includes	Anti-glare housing Suction pads for windshield or rear window mounting

Models available :

Amber FL12A		
Lights	4 lights	2 lights
item n°	18776	24652