

Led Work Light

Led Work Light
Article number : 22433



Technical properties :

Power : 12 W
Consumption : 1A at 12 V / 0.5 A at 24 V
Mechanical specifications : 4 high-luminosity LEDs
Brightness : 200 lux at 1m - angle : +/- 15° Horizontaly & Verticaly (round beam)
Operating temperature : -40°C to +85°C
Color temperature : 3150°K
Aluminium casing - polycarbonate lens - IP66 - IK08

Suction mounted work light

Input Voltage : 10V/30V DC
Dimensions : HxLxW) in mm : 33x106x40
Mounting : by M4 screw on the back and M5 screw on the sides
Delivered with bolts and screws

Approvals :

EMC approvals according to directive 2006/08
(no.e2*72/245*2006/28*09013) & regulation R10 (E2 10R03 09013) -
CISPR25 (2002) : according to the class 3 from 0.15 to 1000MHz radiating

Models available :

	#Article
Projoled without mounting	22433
Projoled with universal mounting	23315
Magnetic Projoled (5-m cable)	23489
Magnetic Projoled (spiral cable)	24171
Magnetic Battery-operated Projoled	23488

Lens	Polycarbonate
Housing	Aluminium
Colour LEDs	White
Colour lens	Crystal
No. of LEDs	4 high-luminosity LEDs
Voltage	10-30V
Consumption	1A : 12V 0,5A : 24V
Length	33 mm
Height	106 mm
Width	40 mm
Operating temperature	-40° - +85°C
Enclosure rating	IP66 - IK08
Colour Temperature	3150K
Luminous flow	200 lux at 1m - angle : +/- 15° Horizontaly & Verticaly (round beam)
Approval	ECE R10, EMC
Includes	bolts and screws
Origin of product	Europe
Guaranty	3 years

ACCESSORIES

	#Article
12V charger with DIN cigar lighter plug	23710
220V charger	23709

Battery-Powered version :

Directional with Ni-Mh Battery
Delivered with a 12V charger & Cigar lighter plug
Battery Charge : 4 hours (without recharge)
Plug and Switch of waterproof recharge

Magnetic version :

Directional with magnetic mounting and universal cigar lighter plug
5-m cable