

Standby-Mercura 4 Rue Louis Pasteur ZA Les Gailletrous 41260 LA CHAUSSEE SAINT VICTOR - FRANCE Tél. +33(0)2 54 57 52 52 - Fax +33(0)2 54 56 80 00 - export@standby-mercura.fr - www.standby-mercura.fr

Magnetic Triangle 500

Magnetic triangle 500 with or without Gyroled M80 Article number: 31874









- Magnetic triangle unit with manual or electric raising system with or without Gyroled M80
- Easy and quick installation with its magnetic fixing system and cigarette lighter plug
- For triangles with electric raising system: protective corrosionresistant aluminium casing
- Electric actuator for bringing quickly the triangle into service from the driver seat, regardless its position on the vehicle
- Day/night adjustment of light intensity by a light sensor

Technical specifications:

- Input voltage: 12/24V
- 500 mm triangle equipped with an obstacle protection hinge
- 74 mm amber LED lights: photometry 964 candelas / light
- Screen print symbol: AK5 (road works)
- Complies with class L2H according to standard EN 12352
- Gyroled M80 amber Class 1 R65 approved: rotating mode by default (13 flash patterns available programmable by the user)
- Cigarette lighter plug: standard 1 button or 1 button with On / off indicator light or double button (triangle / gyroled) with indicator light -see details at the bottom of the page-

Lens Polycarbonate

Colour lens Amber

Colour LEDs

Flash Patterns Gyroled M80: rotating mode

by default

Amber

Cable Length: 5m or 5.5m

depending on the chosen

version

Mounting Magnétique

 Voltage
 10-30V

 Approval
 ECE R65 I

Triangle	Class	Raising system	Cable length	Gyroled	Code
	T1	Manual	5.5m	-	31874
	T2	Manual	5.5m	-	32849
	T1	Electric	5m	-	32850
	T2	Electric	5m	-	32851
	T1	Manual	5.5m	2 x M80	32852
	T2	Manual	5.5m	2 x M80	32853
	T1	Electric	5.5m	2 x M80	33014
	T2	Electric	5.5m	2 x M80	33015





