

ML61 and ML71 Lightbars

2 amber rotating or flashing Gyroled

Article number : 24635



Avantages :

- High Brightness LED technology
- Five times lower power than a conventional lightbar
- Service life of 50.000 hours (considering daily use of 10hours, the LED has a service life of 13 years)
- No belt driven mechanism : maintenance free
- Gyroled approved R65 amber rotating or flashing
- Easy to install
- Anodised aluminium structure anti-corrosion
- Casing in polycarbonate : its great transparency and excellent impact resistance make polycarbonate the best material for the production of automotive lighting components
- User comfort : noise level 0db
- Used by the National Police on all their vehicles.

Technical characteristics :

- Length 1.10m (width 280mm, height 135mm)
- Four amber rotating Gyroleds
- ML6x Series amber rotating Gyroleds
- ML7 Series amber flashing Gyroleds
- Input Voltage : 12/24 V
- Siren : available tones : please click [here](#) to see our different tones available
- Built-in Loudspeaker
- Lightbar controlled by a conventional assembly with switch, fuse relays
- With 10m vehicle cable harness
- Delivered with matt black universal permanent mountings with anti-corrosion treatment

Approval :

PHOTOMETRY : Approval according to regulation ECE-R65

Amber Gyroleds in rotating mode (Beacon light) TA1 (E2) 00 09031

Amber Gyroleds in flashing mode (double flashing) TA1 (E2) 00 09032

Siren approved according to tone : please consult us

Options :

- Waterproof roof connector
- Screen printed text
- Length 1.50m for a commercial vehicle
- Public Address(PA) et recorder with 3 messages
- Controlled by CCS6 (not included, please consult us)
- Tones

Lens	Polycarbonate
Colour LEDs	White
Colour lens	Amber
No. of LEDs	2 Amber Gyroled®
Flash Patterns	ML6x Series amber rotating Gyroleds ML7x Series amber flashing Gyroleds
Voltage	10-30V
Length	1.10 m or 1.50 m
Height	135 mm
Width	280 mm
Approval	ECE R65 I
Includes	Matt black universal permanent mountings with anti-corrosion treatment

ML61 - 2 amber rotating Gyroled

	Gyroled	Length	Loudspeaker	Siren	Roof connector	#Article
ML61	2	1.10m	-	-	-	24635
ML61	2	1.50m	-	-	-	25058
ML61	2	1.10m	-	-	yes	24829
ML61	2	1.50m	-	-	yes	25161
ML61S	2	1.10m	yes	yes	-	CU
ML61S	2	1.50m	yes	yes	-	CU
ML61S	2	1.10m	yes	yes	yes	23605
ML61S	2	1.50m	yes	yes	yes	24444

ML 71 - 2 amber Gyroled double flash

	Gyroled	Length	Loudspeaker	Siren	Roof connector	#Article
ML71	2	1.10m	-	-	-	CU
ML71	2	1.50m	-	-	-	CU
ML71	2	1.10m	-	-	yes	25444
ML71	2	1.50m	-	-	yes	CU
ML71S	2	1.10m	yes	yes	-	CU
ML71S	2	1.50m	yes	yes	-	CU
ML71S	2	1.10m	yes	yes	yes	CU
ML71S	2	1.50m	yes	yes	yes	CU