

ORION lightbar with Gyroleds

LED lightbar approved R65 Europe

Article number : 24976



LED lightbar approved R65 Europe

Advantages:

- LED technology: consumes 5 times less energy than the classic lightbar
- Gyroled without belt: maintenance free
- Product ECE R65 approved
- Light-weight and easy to install
- Polycarbonate casing which allows a high impact resistance
- User comfort with a sound level of 0 decibels

Technical specifications:

- Height: 115 mm / Height with support: 172 mm, Width: 338 mm
- 2 or 4 blue rotating Gyroled
- 2 or 4 amber rotating Gyroled
- Rotating or flashing Gyroled
- Illuminated text
- Input voltage: 12V/24V

Lens	Polycarbonate
Colour LEDs	Amber
No. of LEDs	2 or 4 amber Gyroled®
Flash Patterns	Gyroled® Rotating or Flash
Voltage	10-30V
Length	1.20 commercial vehicles
Height	Height : 115mm Height with support : 172mm
Width	338mm
Approval	ECE R65 I

Available options:

- Lightbar controlled by a conventional assembly with switch, fuse relays (not included)
- With 10 cable harness and roof connector
- Delivered with matt black universal permanent mountings

Length (in mm)	Colour	Gyroled	Mode	Code
1.20	Blue	2	Rotating	24960
1.20	Blue	4	Rotating	24962
1.20	Blue	2	Flashing	24964
1.20	Blue	4	Flashing	24966
1.40	Blue	2	Rotating	24968
1.40	Blue	4	Rotating	24970
1.40	Blue	2	Flashing	24972
1.40	Blue	4	Flashing	24974

Available in 1.60 m, consult us.

For more information, please consult the "documentation" tab below and find our product approvals [here](#).

