

 $Standby-Mercura\ 4\ Rue\ Louis\ Pasteur\ ZA\ Les\ Gailletrous\ 41260\ LA\ CHAUSSEE\ SAINT\ VICTOR\ -\ FRANCE\ Tél.\ +33(0)2\ 54\ 57\ 52\ 52\ -\ Fax\ +33(0)2\ 54\ 56\ 80\ 00\ -\ export@standby-mercura.fr\ -\ www.standby-mercura.fr\ -\ w$

Blue Gyroled for Airports

The LED Beacon with ICAO & EASA Standards for Airports
Article number: 28407



Light meeting the specifications of Annex 14 (Convention on International Civil Aviation of ICAO regulations for vehicles and mobile obstacles like C) and the EASA (Annex to ED Decision 2014/013/R - Certification Specifications (CS) and Guidance Material (GM) for Aerodromes Design - CS-ADR-DSN).





Advantages:

• Light-emitting diode (LED) technology for high brightness • Energy saving: thanks to reduced consumption • Can be used with the engine off • No maintenance! No belt or motor, nor expensive strobe bulb to change • Reduced wear on the vehicle's electrical components: battery, alternator ... • Sturdy due to its dome and polycarbonate parabola • No electromagnetic interference (EMC) • Silent: emits no noise in operation, optimum sound discretion

Colour	Version	Mount	Code
Blue	Rotating	Iso base	28407
		Pipe-mount	28408
		Magnetic	28409
	Flash	Iso base	28410
		Pipe-mount	28411
		Magnetic	28412

Lens Polycarbonate

Colour LEDs Blue
Colour lens Blue

Flash Patterns Rotating or Flash

Voltage 10-30V

Consumption 12 V : 900mA 24 V : 450mA

Diameter Light only: 105,6mm

ISO: 146mm

Height Light only: 64.4mm

ISO:109,4mm

Operating temperature -40°C - +85°C

Enclosure rating IP 45

Approval ECE R65 I, ECE R65 II, ICAO

Annex 14

Origin of product Europe
Guaranty 3 years