

MLX4 Priority Light-Bar

Our "M" lightbars are noted for their aerodynamic shape and their resistance to impacts !
Article number : 20078



Our "M" lightbars are noted for their aerodynamic shape and their resistance to impacts !

Technical specifications :

Length : 1.10m or 1.50m - 12V/24V
Lightbar available with siren, loudspeaker, public address and amber rear traffic director light
Text (to be specified)
100 W Siren in white central part (Tone to be specified, click [here](#) to see the different tones available)
4 Blue Rotating Synchronised Gyroled - 2 at each ends and 2 on the inferior part of the lightbar
Rear Traffic Director Light by 6 amber LED Light (width : 123 mm, Height : 35 mm, 6 LED per light) (Right-Left Scrolling, Warning = full bar)
Wiring Loom with roof connector
Angled connector - 10m vehicle cable harness with fixed base by locknut
Matt Black Mounting 2 alloy LED lights (Projoled)

Approvals :

- Class 1 approved TB1 (E2) 0012033
- Class 2 approved TB2 (E2) 0012198
- Gyroled approved by R65 N° B1 E2 00011

For the PA lightbars :

Control by DIN Audio PA Public Address Metal Microphone with a potentiometer built into it
Control of integrated grill lights
Powering output for the radio

MLx4

Length	Loudspeaker	Siren	PA	Roof connector	Beacons	Lights	Other	#Article Class 1	#Article Class 2
1,50 m	yes	yes	yes	yes	Scrolling	Alley	12 keys	20079	25090
1,10 m	-	-	-	yes	Warning	-	-	26545	CU
1,10 m	-	-	-	yes	Warning	Alley	-	CU	25753
1,10 m	yes	yes	-	yes	Warning	-	-	23117	23714
1,10 m	yes	yes	-	yes	Warning	Alley	-	24313	24371
1,10 m	yes	yes	yes	yes	Scrolling	Alley	12 keys	26925	24240
1,50 m	-	-	-	yes	Warning	Alley	-	CU	23713
1,50 m	-	-	-	yes	Warning	-	-	24681	24675

Lens	Polycarbonate
Colour LEDs	Blue, White
Colour lens	Blue
No. of LEDs	4 Blue Rotating Synchronised Gyroled 2 at each ends and 2 on the inferior part of the lightbar
Voltage	10-30V
Length	1,10 m or 1,50m
Approval	ECE R65 I
Origin of product	Europe
Guaranty	3 years