

MS-350

for undercover application (121dB (A) in 3,5m)

Article number : 31603



For undercover application

Advantages :

- latest digital switchgear technology
- very powerful (**121dB (A) in 3,5m**)
- 3 independently configurable audio inputs (e.g. microphone, radio and line)
- 10 control inputs and 2 power outputs. Additional 4 input/output ports can be configured depending on the application

Available tones :

Voltage	12V, 24V
Consumption	In standby mode : <500mA Maximum : 5A (without beacon)
Maximum current output	12V : 2 x 50W (120W max) 24V : 2 x 80W (200W max)
Dimensions	MS-350 : 44,6 x 136,6 x 131 mm
Diameter	K-SR 350 : 109,25 x 68mm
Weight	MS-350 : approx. 400g K-SR 350 : approx. 850g
Inputs	9 < 20mA (programmable, high-side) 1 < 20mA (programmable, low-side)
Outputs	2 x 5A (programmable) 1 x <2A ; (programmable, also usable as input)
Operating temperature	MS-350 : -25°C à +70°C K-SR 350 : -25°C à +60°C
Enclosure rating	IP54

	Wail, Yelp,Hi-Lo,Horn
	Land, Stadt,US Yelp (DIN14610)
	Swiss tones (Annexe 11 sc 3 -ord 19/06/1995)
	Feuerwehr,Rettung, Polizei
	Ambulanza,Vigili del Fuoco
	UMH, Police, Gendarmerie, Sapeurs-Pompiers, ASA

Others tones available (for Finland, Netherlands, Norway, Sweden) and more programmable options on request.

Approval :

- CEM : E1-047152 (EMV)

References :

Item n°	Name
31601-00	Kit MS-350 (12V), with 1x LS K-SR350 - 4 Ohms and connections
31602-00	Kit MS-350 (24V), with 1x LS K-SR350 - 16 Ohms and connections
31603-00	Kit MS-350 (12V), with 2x LS K-SR350 - 4 Ohms and connections
31604-00	Kit MS-350 (24V), with 2x LS K-SR350 - 16 Ohms and connections

For more technical information and see all possible configurations, please consult documents to download below.