

Standby-Mercura 4 Rue Louis Pasteur ZA Les Gailletrous 41260 LA CHAUSSEE SAINT VICTOR - FRANCE Tél. +33(0)2 54 57 52 52 - Fax +33(0)2 54 56 80 00 - export@standby-mercura.fr - www.standby-mercura.fr

Pack CCS 4 LS

Light and Sound Article number: 28286



Light and Sound

Technical specifications:

- CAN communication ports of which one is used to connect the handy control panel microphone

- Input:
 - Hand-brake
 - o Horn
 - o Crew manager pedal
 - + After ignition or engine running (for the functions: Start-up / Automatic Standby mode)
- Output:
 - o 3.5A output (3 Gyroled®)
 - o Compatible with 4 Ohms or 8 Ohms loud-speakers
- Protection :
 - Against reverse polarity
 - Against high temperatures, automatic temperature control if internal temperature exceeds 95°C
 - Open load detection on the loud-speaker output to guarantee that the siren is activated and in good working order

Voltage 10-30V

 $\begin{tabular}{ll} \textbf{Consumption} & When off: 200 μA: 12V \\ \end{tabular}$

Operating 80 mA:12V

 Weight
 110 g

 Length
 140 mm

 Height
 33 mm

 Depth
 64 mm

Inputs

Horn

Hand-brake

Crew manager pedal + Accessories or engine running (for the functions : Start-up / Automatic Standby

mode)

Outputs 3.5A output (3 Gyroled®)

Compatible with 4 Ohms or 8

Ohms loud-speakers

Operating temperature -40°C - + 85°C

Enclosure rating IP42

IK08

- Power module dimensions (L x H x W in mm): 140 x 33 x 64
- Weight 110 g
- The Information transmission Protocol between the control panel and the CCS power module meets vehicle CAN norms
- Vehicle wiring: CPT connector for the CAN BUS
- IP42, IK08
- Power Supply 10-30 V
- Operating temperature -40°C to + 85°C


Control box:

- 4 control keys
- 1 button On/Off
- 1 battery alarm indicator
- · Pictograms of screen printed buttons adapted to equipment

The kit is made of:

- 1 control panel 4 buttons
- \bullet 1 x mounting to hold the control panel
- 1 BUS connector of 4.5 m
- 1 power module : This module has the following functions : Siren tone amplifier and 3.5A output
- Operating instructions

CCS4 LS technical diagram:



Pack available with **US tone,** with 150W Loud Speaker.

Description	Tone	Loud Speaker	#article
CCS 4 LS US	US Wail, Yelp, Hi-lo, Horn	150W	28869-00

Pack available with **Police tones,** with 30W or 150W Loud Speakers.

Description	Tone	Loud Speaker	#article
CCS 4 LS	Police	150 W	29003
CCS 4 LS	Police	30 W	29361

Pack available **without control panel** but with switches on the dashboard:

Description	Tone	For HP	#article
CCS 4 LS control by switches	To be indicated	30W	29829
CCS 4 LS control by switches	To be indicated	150W	29830