

CCS 4 LS

Mercura presents its new generation multifunctional module. The most compact module currently on the market!

Incorporates emergency vehicle signalling functions: blue beacons and siren.





Functions:

- Siren tone amplifier
- Loud-speaker output protected against short-circuits.
- Power outputs protected against short circuits: Beacons
- Control panel with back-lighting
- Laser etched symbols so that symbol does not rub off
- Fault information
- Easy to mount

- **<u>Automatic system start-up</u>** when the vehicle ignition is switched on (1)
- <u>Automatic Standby mode</u> when the vehicle ignition is switched off, to avoid draining the battery (1)
- Siren and signalling control using the (<u>Horn</u>) warning device and/or the crew manager pedal (<u>Crew manager pedal</u>) (1)

(1) These functions are optional, not compulsory and are activated by the system installer solely following specific wiring instructions. Ref user and mounting instructions.



MERCURA Standby Group

CCS 4 LS



Technical specifications

• CAN communication ports of which one is used to connect the handy control panel microphone

• <u>Input</u>:

Hand-brake, horn, crew manager pedal, +
After ignition or engine running (for the functions:
Start-up / Automatic Standby mode)

Output:

3.5 A output (3 Gyroled®)

 $_{\odot}$ Compatible with 4 Ohms or 8 Ohms loud-speakers

• Protection:

Against reverse polarity

 $_{\odot}$ Against high temperatures, automatic temperature control if internal temperature exceeds 95°C.

 $_{\odot}$ Open load detection on the loud-speaker output to guarantee that the siren is activated and in good working order.

• Power module dimensions: (L x H x W in mm) : 140 x 33 x 64

• Weight 110 g

• The Information transmission Protocol between the control panel and the CCS power module meets vehicle CAN norms

• Vehicle wiring: CPT connector for the CAN BUS

- IP42, IK08
- Power Supply 10-30 V
- Operating temperature -40°C to + 85°C

Approvals:

Product designed and developed according to current vehicle norms (electrical, EMC, physico-chemical...)

EMC approval according to regulation 10R04 under n° "E2 04 11026"

Acoustics: Approval carried out by the UTAC.

The kit is made of:

- 8 button control panel
- 1 dashboard mounting system
- 1 BUS connector of 4.5 m
- 1 power module: This module has the following functions : Siren tone amplifier and 3.5 A output
- Operating instructions

| Description | Tone | Loudspeaker | #article |
|-----------------------|-------------------------|-------------|----------|
| CCS4 LS International | Wail, Yelp, Hi-lo, Horn | 30 W | 32733-00 |
| CCS4 LS International | Wail, Yelp, Hi-lo, Horn | 150 W | 32734-00 |

Warranty: 3 years

