

BATTERY OPERATED GYROLED *Stick (Suction mount)*

Advantages:

- Rotating or flashing R65 approved beacon
- Light-Emitting Diode Technology (LED)
- No more maintenance! No belt, no motor, no expensive flashing light to be replaced
- Less wear on the electrical parts of the vehicle: battery, alternator, etc.
- Robust: dome and parabola in Polycarbonate
- No electromagnetic interference (EMC)
- Quiet: no noise when operating
- 4 hours-autonomy
- Charge or remaining autonomy indicator
- Delivered with 12V or 220V plug



Technical specifications

- Height 239 mm – diameter 119 mm
- Operating temperature: -40°C to +85°C
- Input voltage: from 10 to 30V
- Protected against polarity reversion
- Consumption:
 - 12V: 900mA
 - 24V: 450mA
- Battery: Lithium polymer (21.6V 2.9A)



Full battery
Green indicator



Empty battery
Red indicator

Approvals

EMC:

DIRECTIVE 2006/28 n°e2*72/245*2006/28*08036
Complies with CISPR25 (2002) class 3 (rotating mode)

PROTECTION:

Protection against mechanical impacts: IK08 according to NF EN 50102

PHOTOMETRY: Approval according to regulation R65

90 candelas: min. value guaranteed through 360° on the horizontal plane 0°
200 candelas: max. value on the horizontal plane 0°

ELECTRICAL:

ISO 7637-2(2004), Technical specifications PSA B21 7110 (2001) & Renault 36-00-808/___E (2001)

BATTERY OPERATED GYROLED *Stick (Suction mount)*

Designation	Mode	Colour	#article
Stick battery operated Gyroled <i>Plug 12 V</i>	Rotating	Blue	24487
		Amber	24491
		Red	24499
		Green	24495
	Flash	Blue	24488
		Amber	24492
		Red	24500
		Green	24496

Designation	Mode	Colour	#article
Stick battery operated Gyroled <i>Plug 220 V</i>	Rotating	Blue	-
		Amber	-
		Red	-
		Green	-
	Flash	Blue	-
		Amber	-
		Red	-
		Green	-

Accessories	#article
12V cigar lighter plug	23710
220V plug	23709