



Magnetic Triangle 500

With or without Gyroled M80







- Easy and quick installation with its magnetic fixing system and cigarette lighter plug
- For triangles with electric raising system: protective corrosion-resistant aluminium casing
- Electric actuator for bringing quickly the triangle into service from the driver seat, regardless its position on the vehicle
- Day/night adjustment of light intensity by a light sensor

Technical specifications

- Input voltage: 12/24V
- 500 mm triangle equipped with an obstacle protection hinge
- 74 mm amber LED lights: photometry 964 candelas / light
- Screen print symbol: AK5 (road works)

- Complies with class L2H according to standard EN 12352
- Gyroled M80 amber Class 1 R65 approved: rotating mode by default (13 flash patterns available programmable by the user)
- Cigarette lighter plug: standard 1 button or 1 button with On / off indicator light or double button (triangle / gyroled) with indicator light -see details at the bottom of the page-

Triangle	Class	Raising system	Cable length	Gyroled	Code
A	T1	Manual	5.5m	-	31874
	Т2	Manual	5.5m	-	32849
B	T1	Electric	5m	-	32850
	T2	Electric	5m	-	32851
C	T1	Manual	5.5m	2 x M80	32852
	T2	Manual	5.5m	2 x M80	32853
B	T1	Electric	5.5m	2 x M80	33014
	T2	Electric	5.5m	2 x M80	33015





Standard cigarette lighter plug with 1 backlit button





Cigarette lighter plug with on/off indicator light





Cigarette lighter plug with double button with indicator light